

		ERVX-150 inv	ERVX-250 inv	ERVX-350 inv	ERVX-600 inv	ERVX-800 inv	ERVX-1000 inv	ERVX-1300 inv
Temperatūrinis rekuperatoriaus naudingumo koeficientas	%	80	73	76	70	68	70	70
Energetinis efektyvumas		A	A	A	A	A	A	A
Oro srautas prie 0 Pa	m ³ /h	210	345	500	690	980	1150	1700
Oro srautas prie 100 Pa	m ³ /h	150	250	350	600	800	1000	1300
Automatinis "Bypass"		-	-	-	+	+	+	+
Automatinis "Defrost"		+	+	+	+	+	+	+
Maksimalus naudojamas el. galinumas	W	65	95	155	162	290	327	424
Įtampa / dažnis	V/Hz	230/50	230/50	230/50	230/50	230/50	230/50	230/50
Garso lygis	dB(A)	31,5	34	37	39	41	42	43
Įrenginio svoris neto	kg	29	32	42	34	53	61	71
Svoris pakuotėje	kg	33	36,5	47				
Matmenys plotis/aukštis/ilgis	mm	685/220/860	700/220/830	820/230/1070	902/280/867	884/388/1134	1134/388/1134	1173/388/1193
Ortakio skersmuo	mm	98	144	144	194	242	242	242
Rekomenduojamas el. pašild. galinumas (13oC)	W	390	1000	1400	2200	3800	4800	4800